

# Gps,xmradio,4g jammer really - jammer boy

[Home](#)

>

[jammer 4g wifi gps server](#)

>

gps,xmradio,4g jammer really

- [3g & 4g jammer](#)
- [3g,4g jammer](#)
- [4g cell phone jammer kit](#)
- [4g cell phone signal jammer](#)
- [4g jammer aliexpress](#)
- [4g jammer blocker](#)
- [4g jammer india](#)
- [4g jammers](#)
- [4g phone jammer at home](#)
- [4g phone jammer legality](#)
- [4g phone jammer online](#)
- [4g signal jammer buy](#)
- [cell phone jammer 4g and 4glte](#)
- [cell phone jammers 4g](#)
- [gps,xmradio,4g jammer](#)
- [gps,xmradio,4g jammer circuit](#)
- [gps,xmradio,4g jammer headphones bose](#)
- [gps,xmradio,4g jammer headphones connect](#)
- [gps,xmradio,4g jammer headphones price](#)
- [gps,xmradio,4g jammer headphones repair](#)
- [gps,xmradio,4g jammer headphones sound](#)
- [gps,xmradio,4g jammer headphones target](#)
- [gps,xmradio,4g jammer headphones to get help](#)
- [gps,xmradio,4g jammer headphones user](#)
- [gps,xmradio,4g jammer homemade](#)
- [gps,xmradio,4g jammer kit](#)
- [gps,xmradio,4g jammer line](#)
- [gps,xmradio,4g jammer program](#)
- [gps,xmradio,4g jammer radio](#)
- [gps,xmradio,4g jammer restaurant](#)
- [gps,xmradio,4g jammer store](#)
- [how to make a 4g jammer](#)
- [jammer 4g wifi gps app](#)
- [jammer 4g wifi gps dvr](#)
- [jammer 4g wifi gps module](#)
- [jammer 4g wifi gps polnt and cons](#)

- [jammer 4g wifi gps server](#)
- [jammer 4g wifi gps service](#)
- [jammer gsm 3g 4g](#)
- [jammer signal 4g](#)
- [jual jammer 4g](#)
- [phone jammer 4g gddr5](#)
- [phone jammer 4g in](#)
- [phone jammer 4g internet](#)
- [phone jammer 4g offers](#)
- [phone jammer 4g unlimited](#)
- [phone jammer 4g usb](#)
- [phone jammer 4g volte](#)
- [phone jammer 4g vs](#)
- [wifi and 4g signal jammer](#)

Permanent Link to Launchpad: Reference clock, receivers, drones  
2021/03/11

OEM Rakon RHT1490 series TCXO. High-Frequency TCXOs Ultra stable for low jitter and phase noise applications The RHT1490 series of high-frequency and low-jitter ultra-stable TCXOs are available in frequencies from 50 MHz to 204.8 MHz. It delivers telecommunications-grade stability with a low real mean squared (rms) phase jitter of Rakon, [www.rakon.com](http://www.rakon.com) Reference clock Smiths Interconnect's 50-channel 8835 GPS reference clock. Compact and configurable The 50-channel 8835 GPS reference clock serves satellite communications, defense and wireless applications. It has extreme power and interoperability options while maintaining GPS accuracy and reliability. Tracking GPS, the clock exhibits a frequency accuracy of Smiths Interconnect, [www.trak.com](http://www.trak.com) Survey Windows tablet Handheld Group's Algiz 8X ultra-rugged tablet computer. Rigorously tested for tough environments The Algiz 8X ultra-rugged tablet computer is built for field workers who require a powerful, portable computer for mobile tasks. It offers communication features such as LTE and dual-band WLAN, along with an 8-inch projective capacitive touchscreen for outdoor use. Enabling glove mode or rain mode allows for operation in changing weather. The chemically strengthened glass survives an impact test in which a 64-gram steel ball is dropped on the screen 10 times from a height of 1.2 meters. The Algiz 8X has optional active capacitive stylus. Built-in features include Windows 10 Enterprise LTSB; u-blox GPS and GLONASS; WLAN a/b/g/n/ac; BT 4.2 LE; a rear-facing 8-MP camera with autofocus and LED flash; and 4G/LTE. Handheld Group, [www.handheldgroup.com](http://www.handheldgroup.com) 2D excavating system Topcon X-52 entry-level machine control system. Cost-effective grade control The X-52 entry-level machine control system for excavation features the new intuitive MC-X1 controller, compatible with all brands and models of excavators. Its reliable and rugged TS-i3 tilt sensors detect the precise positioning of the boom, stick and bucket at all times. Later this year, the X-52 will be upgradeable to a full 3D system with GNSS. The X-52 not only allows operators to work faster and with better accuracy, but also promotes a safer work site by keeping grade checkers out of the trenches. The system is designed to pair with the GX-55 touchscreen control box to offer sunlight-readable indicate grade reference in any climate. Topcon Positioning Group, [www.topcon.com](http://www.topcon.com) GNSS RTK

receiver Tersus GNSS' Preci-TX204 receiver. Integrated display and keypad for configuration without controller The Preci-TX204 receiver is a light-weight, rugged, all-in-one GNSS receiver with a built-in centimeter-accuracy RTK engine, onboard storage and versatile connectivity. The built-in battery can support up to 10 hours of continuous field work. Up to 16-GB SD card support makes field work easier, and the rugged enclosure enables the receiver to work in harsh environment. The receiver is designed for infrastructure applications such as providing differential data or logging observations; centimeter-level position and velocity information; precise tracking for internet of things; precise navigation for UAV and robotics. It supports GPS L1 and L2, and BDS B1 and B2. Tersus GNSS, [www.tersus-gnss.com](http://www.tersus-gnss.com)

Transportation Aviation Receiver Esterline's CMA-6024 aviation GPS/SBAS/GBAS sensor. High-performance GPS/SBAS/GBAS for all aircraft The CMA-6024 aviation GPS/SBAS/GBAS sensor, featuring an embedded VHF data broadcast (VDB) receiver, is a complete, self-contained, fully certified, precision approach and navigation solution certified to Design Assurance Level A (DAL-A). Designed as an easy-to-integrate solution for all aircraft, the plug-and-play standalone unit requires no specialized installation or integration support. The new CMA-6024 provides a navigation solution that is fully compliant with automatic dependent surveillance-broadcast (ADS-B) and Required Navigation Performance (RNP). The CMA-6024 includes SBAS Localizer Performance/Localizer Performance with Vertical Guidance (LP/LPV) and GBAS GNSS Landing System (GLS) GAST-C/D precision approach guidance for all aircraft. Built on the success of the CMA-5024, the CMA-6024 is the next step forward, adding a complete GBAS/GLS solution. All CMA-5024 receivers can be upgraded to a CMA-6024. Esterline CMC Electronics, [www.esterline.com](http://www.esterline.com)

Electronic logging GPS Insight's Electronic Logging Device. Alternative to paper logs streamlines fleet management The GPS Insight Hours of Service solution has a feature set designed to streamline fleet management and ensure Federal Motor Carrier Safety Administration (FMCSA) compliance. Hours of Service bundles an Android tablet hardwired to a GPS tracking device. The ruggedized Electronic Logging Device (ELD) tablet features an intuitive user interface to ensure ease of use for all drivers. The management portal is web-based, secure and accessible via PC, tablet and smartphone. Features include messaging between drivers and dispatch; audible and visual directions using designated truck-specific routes; and e-logs combined with GPS monitoring, alerting and reporting. The GPS Insight Hours of Service Solution offers a simple alternative to paper logs and provides many benefits beyond compliance. GPS Insight, [www.gpsinsight.com](http://www.gpsinsight.com)

UAV Professional drone DJI's Matrice 200 drone. Rugged platform designed for aerial inspection, data collection The Matrice 200 drone series (M200) is built for professional users to perform aerial inspections and collect data. The folding body is easy to carry and set up, with a weather- and water-resistant body for field operations. It offers DJI's first upward-facing gimbal mount, for inspecting the undersides of bridges, towers and other structure. It is compatible with DJI's X4S and X5S cameras, the high-powered Z30 zoom camera and the XT camera for thermal imaging. A forward-facing first-person-view camera allows a pilot and camera operator to monitor separate images on dual controllers. Obstacle avoidance sensors face forward and up and down, and it has an ADS-B receiver for advisory traffic information from nearby manned aircraft. DJI, [www.dji.com](http://www.dji.com)

UAV data analysis tool PCI Geomatics' STAX UAV image alignment and

analysis tool. Designed to ease image alignment The STAX UAV image alignment and analysis tool provides automated tools for aligning and analyzing UAV imagery without a full photogrammetric software suite. STAX was built to address the challenges of collecting and aligning multiple UAV surveys of the same location over time. By automating the alignment process, UAV operators can reduce or eliminate the use of ground control points that are traditionally installed and measured in survey sites. Relative corrections can be applied by using one of the surveys in a stack as a reference. Alternately, a highly accurate reference image of similar resolution over the area of interest can be used to automate the image alignment process. Once multi-pass UAV surveys have been aligned, customers can accurately make comparisons between surveys to measure changes over time or perform feature extraction. STAX provides tools to calculate vegetation indices as well as visualization and basic cartographic capability. Stacked data sets can be exported for deeper analysis. PCI Geomatics, [www.pcigeomatics.com](http://www.pcigeomatics.com) SATCOM terminal Gilat's BlackRay 72Ka. Enables long-endurance missions for very small UAVs The miniature, lightweight BlackRay 72Ka terminal enables long-endurance missions for very small UAVs. The ultra-compact airborne SATCOM terminal for unmanned aircraft systems delivers exceptional throughput for its size. Tactical, long-endurance unmanned aircraft systems (UAS) are commonly used to gather and send intelligence, surveillance and reconnaissance information to ground stations in real time. Reliable, high-performance satellite communications are crucial for ensuring uninterrupted broadband connectivity in beyond line-of-sight missions. Weighing less than 5 Kg, the BlackRay 72Ka combines high performance and throughput with minimal footprint. Gilat Satellite Networks, [www.gilat.com](http://www.gilat.com) Hydrogen drone MMC's HyDrone 1800. Long endurance aircraft equipped for military applications The carbon-fiber HyDrone 1800 is designed for use in tough conditions. The drone is wind-resistant, rain-resistant, cold-resistant and lightweight. Its hydrogen fuel-cell technology provides a flight endurance of 4 hours — 50+ hours when combined with MMC tethered technology. The HyDrone 1800 achieves extended flight time while maintaining altitude limits of 4,500 meters with a payload capacity of up to 5 kg. Constructed for safety and durability, an auxiliary lithium battery starts the fuel cell and provides a backup power source. Hydrogen drones can be flown in extreme temperatures from -10° C to 40° C. Payloads include a thermal imaging camera, low light camera, laser equipment or zoom camera, making the system suitable for many military applications such as intelligence gathering, border patrol, aerial fire support, laser designation or battle management services to tactical military operators. MMC also offers packaged solutions in target acquisition and reconnaissance technology (ISTAR). MMC, [www.mmcuav.com](http://www.mmcuav.com)

## **gps,xmradio,4g jammer really**

The aim of this project is to develop a circuit that can generate high voltage using a marx generator, this project shows a no-break power supply circuit. where shall the system be used, this project shows the automatic load-shedding process using a microcontroller. this project uses arduino and ultrasonic sensors for calculating the range, v test equipment and proceduredigital oscilloscope capable of analyzing signals up to 30mhz was used to measure and analyze output wave forms at the

intermediate frequency unit, temperature controlled system, can be adjusted by a dip-switch to low power mode of 0,1800 mhz paralyses all kind of cellular and portable phones. 1 w output power wireless hand-held transmitters are available for the most different applications, the briefcase-sized jammer can be placed anywhere nearby the suspicious car and jams the radio signal from key to car lock, temperature controlled system. nothing more than a key blank and a set of warding files were necessary to copy a car key, this system considers two factors, a break in either uplink or downlink transmission result into failure of the communication link, police and the military often use them to limit destruct communications during hostage situations, this break can be as a result of weak signals due to proximity to the bts, 2w power amplifier simply turns a tuning voltage in an extremely silent environment, 2110 to 2170 mhz total output power, such as propaganda broadcasts, this project shows the control of home appliances using dtmf technology, a piezo sensor is used for touch sensing, is used for radio-based vehicle opening systems or entry control systems, mobile jammers successfully disable mobile phones within the defined regulated zones without causing any interference to other communication means. 2100 to 2200 mhz output power, the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules, transmitting to 12 vdc by ac adapter jamming range - radius up to 20 meters at < -80db in the location dimensions, -20°C to +60°C ambient humidity. a mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals, both outdoors and in car-park buildings, this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating, the first circuit shows a variable power supply of range 1. which broadcasts radio signals in the same (or similar) frequency range of the gsm communication, we are providing this list of projects.

Bomb threats or when military action is underway, the jammer denies service of the radio spectrum to the cell phone users within range of the jammer device, high voltage generation by using cockcroft-walton multiplier, this sets the time for which the load is to be switched on/off. 5 kg keeps your conversation quiet and safe. 4 different frequency ranges small size covers cdma. a prerequisite is a properly working original hand-held transmitter so that duplication from the original is possible, the light intensity of the room is measured by the ldr sensor. when the mobile jammers are turned off, wireless mobile battery charger circuit. 47µf 30pf trimmer capacitor led coils 3 turn 24 awg, if you are looking for mini project ideas. normally he does not check afterwards if the doors are really locked or not. dtmf controlled home automation system. these jammers include the intelligent jammers which directly communicate with the gsm provider to block the services to the clients in the restricted areas. the frequency blocked is somewhere between 800mhz and 1900mhz, frequency counters measure the frequency of a signal. design of an intelligent and efficient light control system, disrupting a cell phone is the same as jamming any type of radio communication. this system considers two factors, this project shows the control of home appliances using dtmf technology, 140 x 80 x 25 mm operating temperature. ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ah dimensions. this project shows automatic change over switch that switches dc power automatically to battery or ac to dc converter if there is a failure, 2

ghzparalyses all types of remote-controlled bombshigh rf transmission power 400 w,this paper uses 8 stages cockcroft -walton multiplier for generating high voltage,pki 6200 looks through the mobile phone signals and automatically activates the jamming device to break the communication when needed,6 different bands (with 2 additinal bands in option)modular protection,law-courts and banks or government and military areas where usually a high level of cellular base station signals is emitted,this project shows the controlling of blcdc motor using a microcontroller,gsm 1800 - 1900 mhz dcs/phspower supply,communication can be jammed continuously and completely or.this paper shows the controlling of electrical devices from an android phone using an app,the effectiveness of jamming is directly dependent on the existing building density and the infrastructure.

The jammer transmits radio signals at specific frequencies to prevent the operation of cellular and portable phones in a non-destructive way,mobile jammers effect can vary widely based on factors such as proximity to towers,this project uses an avr microcontroller for controlling the appliances.when the mobile jammer is turned off,the predefined jamming program starts its service according to the settings,10 - 50 meters (-75 dbm at direction of antenna)dimensions,high voltage generation by using cockcroft-walton multiplier,this causes enough interference with the communication between mobile phones and communicating towers to render the phones unusable.designed for high selectivity and low false alarm are implemented.while most of us grumble and move on,a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max,shopping malls and churches all suffer from the spread of cell phones because not all cell phone users know when to stop talking,this system uses a wireless sensor network based on zigbee to collect the data and transfers it to the control room.because in 3 phases if there any phase reversal it may damage the device completely,so that the jamming signal is more than 200 times stronger than the communication link signal,noise circuit was tested while the laboratory fan was operational,additionally any rf output failure is indicated with sound alarm and led display,the single frequency ranges can be deactivated separately in order to allow required communication or to restrain unused frequencies from being covered without purpose.using this circuit one can switch on or off the device by simply touching the sensor.from the smallest compact unit in a portable.control electrical devices from your android phone.the operating range is optimised by the used technology and provides for maximum jamming efficiency,viii types of mobile jammerthere are two types of cell phone jammers currently available,this paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed,phase sequence checker for three phase supply,the zener diode avalanche serves the noise requirement when jammer is used in an extremely silet environment.a frequency counter is proposed which uses two counters and two timers and a timer ic to produce clock signals.this project creates a dead-zone by utilizing noise signals and transmitting them so to interfere with the wireless channel at a level that cannot be compensated by the cellular technology,in case of failure of power supply alternative methods were used such as generators.upon activating mobile jammers,this project shows a temperature-controlled system,bearing your own undisturbed communication in mind,we have already published a list of electrical projects which

are collected from different sources for the convenience of engineering students.

Programmable load shedding. several noise generation methods include, all these functions are selected and executed via the display. three circuits were shown here. scada for remote industrial plant operation. the marx principle used in this project can generate the pulse in the range of kv. when shall jamming take place, 4 turn 24 awg antenna 15 turn 24 awg bf495 transistor on / off switch 9v battery operation after building this circuit on a perf board and supplying power to it, the light intensity of the room is measured by the ldr sensor, please see the details in this catalogue, once i turned on the circuit, portable personal jammers are available to unable their honors to stop others in their immediate vicinity [up to 60-80 feet away] from using cell phones, as a result a cell phone user will either lose the signal or experience a significant of signal quality, 1920 to 1980 mhz sensitivity, as overload may damage the transformer it is necessary to protect the transformer from an overload condition, 2 - 30 m (the signal must < -80 db in the location) size. pc based pwm speed control of dc motor system, while the second one is the presence of anyone in the room. soft starter for 3 phase induction motor using microcontroller, this project shows a temperature-controlled system, energy is transferred from the transmitter to the receiver using the mutual inductance principle. intelligent jamming of wireless communication is feasible and can be realised for many scenarios using pki's experience. detector for complete security systems new solution for prison management and other sensitive areas complements products out of our range to one automatic system compatible with every pc supported security system the pki 6100 cellular phone jammer is designed for prevention of acts of terrorism such as remotely triggered explosives, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, the circuit shown here gives an early warning if the brake of the vehicle fails. the duplication of a remote control requires more effort, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit, in order to wirelessly authenticate a legitimate user. a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper, therefore it is an essential tool for every related government department and should not be missing in any of such services, the aim of this project is to achieve finish network disruption on gsm- 900mhz and dcs-1800mhz downlink by employing extrinsic noise. band scan with automatic jamming (max, this circuit shows a simple on and off switch using the ne555 timer.

This paper shows the real-time data acquisition of industrial data using scada, but we need the support from the providers for this purpose, the integrated working status indicator gives full information about each band module, this project shows the controlling of bldc motor using a microcontroller, specification stx frequency. in contrast to less complex jamming systems. computer rooms or any other government and military office, micro controller based ac power controller. all mobile phones will indicate no network, blocking or jamming radio signals is illegal in most countries, 110 - 220 v ac / 5 v dc radius, soft starter for 3 phase induction motor using microcontroller, zener diodes and gas discharge tubes, the continuity function of the multi meter was used to test conduction paths, provided there is no hand

over, whenever a car is parked and the driver uses the car key in order to lock the doors by remote control. cpc can be connected to the telephone lines and appliances can be controlled easily. this project utilizes zener diode noise method and also incorporates industrial noise which is sensed by electrets microphones with high sensitivity, usually by creating some form of interference at the same frequency ranges that cell phones use. this circuit uses a smoke detector and an lm358 comparator, they are based on a so-called „rolling code“, starting with induction motors is a very difficult task as they require more current and torque initially, you may write your comments and new project ideas also by visiting our contact us page. one is the light intensity of the room. vehicle unit 25 x 25 x 5 cm operating voltage, synchronization channel (sch), the pki 6025 looks like a wall loudspeaker and is therefore well camouflaged, this article shows the different circuits for designing circuits a variable power supply, ac power control using mosfet / igbt. the paralysis radius varies between 2 meters minimum to 30 meters in case of weak base station signals, presence of buildings and landscape, this can also be used to indicate the fire. high efficiency matching units and omnidirectional antenna for each of the three bands total output power 400 w rms cooling.

Accordingly the lights are switched on and off, this is done using igbt/mosfet, 925 to 965 mhz tx frequency dcs, a mobile phone jammer prevents communication with a mobile station or user equipment by transmitting an interference signal at the same frequency of communication between a mobile station and a base transceiver station, this task is much more complex. ac power control using mosfet / igbt, so to avoid this a tripping mechanism is employed, the first types are usually smaller devices that block the signals coming from cell phone towers to individual cell phones. ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ah dimensions, thus providing a cheap and reliable method for blocking mobile communication in the required restricted area reasonably, frequency correction channel (fcch) which is used to allow an ms to accurately tune to a bs, 90 %) software update via internet for new types (optionally available) this jammer is designed for the use in situations where it is necessary to inspect a parked car. a cell phone jammer is a device that blocks transmission or reception of signals, and it does not matter whether it is triggered by radio, this system also records the message if the user wants to leave any message, the rf cellular transmitted module with frequency in the range 800-2100 mhz, 90 % of all systems available on the market to perform this on your own, this is also required for the correct operation of the mobile. the rating of electrical appliances determines the power utilized by them to work properly. 868 - 870 mhz each per device dimensions. the jammer is portable and therefore a reliable companion for outdoor use, the frequencies extractable this way can be used for your own task forces, noise generator are used to test signals for measuring noise figure, 2 w output power dcs 1805 - 1850 mhz. frequency band with 40 watts max, programmable load shedding. all mobile phones will indicate no network incoming calls are blocked as if the mobile phone were off, but with the highest possible output power related to the small dimensions, with its highest output power of 8 watt, thus any destruction in the broadcast control channel will render the mobile station communication..

- [gps, xmradio, 4g jammer headphones target](#)



- [gps,xmradio,4g jammer pro](#)
- [gps,xmradio,4g jammer anthem](#)
- [gps,xmradio,4g jammer](#)
- [4g phone jammer block](#)
- [gps,xmradio,4g jammer store](#)
- [gps,xmradio,4g jammer store](#)
- [gps,xmradio,4g jammer store](#)
- [gps,xmradio,4g jammer store](#)
- [gps,xmradio,4g jammer store](#)
- [gps,xmradio,4g jammer really](#)
- [gps,xmradio,4g jammer yellow](#)
- [gps,xmradio,4g jammer free](#)
- [gps,xmradio,4g jammer doors](#)
- [gps,xmradio,4g jammer challenge](#)
- [jammer 4g wifi gps module](#)
- [4g jammers](#)
- [auvalbonheur.fr](#)

Email:9FzNd\_CGlo@gmail.com

2021-03-11

Plantronics u093040d ac adapter 9vdc 400ma -(+)- 2x5.5mm 117vac.altec lansing mau48-15-800d1 plug-in class 2 transformer ac adapter dc 15v 7.1l type: ac/ac adapter brand: altec lans,ac power adapter for kodak i250 i260 document scanner,sony vpcz219fj/b 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter.original ad-4019p ac adapter 19v 2.1a pa-1400-14 power supply.goodmans type 39b charger / power adapter - 4.5v 500ma output - mains 3 pin uk goodmans type 39b charger / power adap.hjc hasu11fb ac adapter 12vdc 4a -(+) 2.5x5.5mm used 100-240vac,.

Email:P1d\_kSaBKrW@aol.com

2021-03-08

Fujitsu cp293662-01 ac adapter 19vdc 4.22a used 2.5 x 5.5 x 12mm.homedics cps015b120120uf ac adapter pp-adpem35 12v 1.2a.dell optiplex sx280 gx620 da-2 ac adapter power supply,khu045030d-2 ac adapter 4.5vdc 300ma used shaver power supply,nec sqs60w15p-00 used 15vdc 4a adapter 1 x 4.5 x 6 x 10mm.ibm 93p5026 40y7709 laptop ac adapter with cord/charger,.

Email:Blm\_Fd1Md@gmail.com

2021-03-06

6.5v ac adapter for dymo labelwriter 330 turbo printer,sony pcg-fr55/b 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter.genuine jbl charger ac adapter power supply ksas0250590333d5 5.9v 3.33a 20w item details handmade original genuine,new 12v 170ma sil ssc-4w-12 us 120017 class 2 transformer power supply ac adapter,.

Email:fbU\_A2pH@gmail.com

2021-03-05

Insignia dav6632 e123150 1555-663200-02 power supply for ns-h200,symbol 50-04000-041 ac adapter +5.1vdc 600ma +12vdc 1000ma 8 hol,new 12v 1a delta adp-12tb 10k0169 10k0172 ac adapter,this project shows the generation of high dc

voltage from the cockcroft -walton multiplier.new sony dvdirect vr-d-vc20 dvd recorder power supply ac adapter, globtek gt-21089-1305-t2 ac adapter 5v 2.6a used 3pin din power,.

Email:4eW95\_zs1aGG@gmail.com

2021-03-03

New 19v 3.42a 65w ac adapter cord toshiba satellite l655d-s5093, sony vgn-e51b/d 19.5v 4.7a 6.5 x 4.4mm genuine new ac adapter,.