

# Jammer gsm 3g 4g | gsm gps jammer on animal

[Home](#)

>

[jammer 4g wifi gps polnt and cons](#)

>

jammer gsm 3g 4g

- [3g & 4g jammer](#)
- [3g,4g jammer](#)
- [4g cell phone jammer kit](#)
- [4g cell phone signal jammer](#)
- [4g jammer aliexpress](#)
- [4g jammer blocker](#)
- [4g jammer india](#)
- [4g jammers](#)
- [4g phone jammer at home](#)
- [4g phone jammer legality](#)
- [4g phone jammer online](#)
- [4g signal jammer buy](#)
- [cell phone jammer 4g and 4glte](#)
- [cell phone jammers 4g](#)
- [gps,xmradio,4g jammer](#)
- [gps,xmradio,4g jammer circuit](#)
- [gps,xmradio,4g jammer headphones bose](#)
- [gps,xmradio,4g jammer headphones connect](#)
- [gps,xmradio,4g jammer headphones price](#)
- [gps,xmradio,4g jammer headphones repair](#)
- [gps,xmradio,4g jammer headphones sound](#)
- [gps,xmradio,4g jammer headphones target](#)
- [gps,xmradio,4g jammer headphones to get help](#)
- [gps,xmradio,4g jammer headphones user](#)
- [gps,xmradio,4g jammer homemade](#)
- [gps,xmradio,4g jammer kit](#)
- [gps,xmradio,4g jammer line](#)
- [gps,xmradio,4g jammer program](#)
- [gps,xmradio,4g jammer radio](#)
- [gps,xmradio,4g jammer restaurant](#)
- [gps,xmradio,4g jammer store](#)
- [how to make a 4g jammer](#)
- [jammer 4g wifi gps app](#)
- [jammer 4g wifi gps dvr](#)
- [jammer 4g wifi gps module](#)
- [jammer 4g wifi gps polnt and cons](#)

- [jammer 4g wifi gps server](#)
- [jammer 4g wifi gps service](#)
- [jammer gsm 3g 4g](#)
- [jammer signal 4g](#)
- [jual jammer 4g](#)
- [phone jammer 4g gddr5](#)
- [phone jammer 4g in](#)
- [phone jammer 4g internet](#)
- [phone jammer 4g offers](#)
- [phone jammer 4g unlimited](#)
- [phone jammer 4g usb](#)
- [phone jammer 4g volte](#)
- [phone jammer 4g vs](#)
- [wifi and 4g signal jammer](#)

Permanent Link to Innovation: GNSS and the Ionosphere  
2021/03/26

What's in Store for the Next Solar Maximum? By Anna B.O. Jensen and Cathryn Mitchell Although the sun can become disturbed at any time, solar activity is correlated with the approximately 11-year cycle of spots on the sun's surface. We are just coming out of a minimum in the solar cycle and headed for the next maximum, predicted to occur around the middle of 2013. How significantly will GNSS users be affected? In this month's column, two ionosphere experts tell us what might be in store. INNOVATION INSIGHTS by Richard Langley "HERE COMES THE SUN / here comes the sun / And I say / it's all right." Is it? Of course, George Harrison was referring to the welcome return of the sun after a long dreary English winter. But can GNSS users sing the same refrain? The signals from global navigation satellites must transit the ionosphere on their way to receivers on or near the Earth's surface. The passage exacts a toll in the form of an added delay of the pseudorandom-noise-code signals and an advance of the phase of the signals' carriers, due to the presence of the ionosphere's free electrons. These perturbations must be ameliorated in some way to achieve high accuracy in GNSS positioning, navigation, and timing applications. Where do the ionosphere's electrons come from? For the most part, they are valence electrons, stripped from upper atmosphere atoms and molecules by the extreme ultraviolet light continuously emitted by the sun. On the Earth's night-side, the electrons and the ionized atoms and molecules tend to recombine. This ionization and recombination process, along with the interactions of the particles with the Earth's magnetic field, governs the density of the electrons at a particular location and time. The ionosphere is also affected by the solar wind, and its associated magnetic field, but the cocoon established by the Earth's magnetic field (the magnetosphere) tends to deflect the solar wind so that it usually has little influence on the ionosphere. Normally, the sun is quiescent: its electromagnetic and particle radiation is fairly constant, and its effects on the ionosphere benign. The delay in GNSS code observations and the advance in phase observations can be readily estimated and removed from the observations using a variety of models and methods. However, the sun can become disturbed, giving rise to occasional violent outbursts with large increases in electromagnetic and particle radiation. These outbursts can

radically change the distribution of the electrons in the ionosphere, reducing the effectiveness of some amelioration methods. The electron density variability can become so rapid that a GNSS receiver can lose lock on satellite signals. And an increase in the sun's radio emissions can become so large as to drown out GNSS signals on the sunlight side of the Earth. Although the sun can become disturbed at any time, solar activity is correlated with the approximately 11-year cycle of spots on the sun's surface. We are just coming out of a minimum in the solar cycle and headed for the next maximum, predicted to occur around the middle of 2013. How significantly will GNSS users be affected? In this month's column, two ionosphere experts tell us what might be in store. GNSS satellite signals are affected by the space environment and the Earth's atmosphere as they travel from satellites at an altitude of about 20,000 kilometers above the surface of the Earth to receivers located at, or close to, the surface. In the upper part of the Earth's atmosphere, the ionosphere, which is located from about 80 to 1,000 kilometers above the surface of the Earth, satellite signals are affected by the free electrons stripped from atoms and molecules by ionization. The signals are refracted by this plasma, which changes their speed of travel. The effect is mainly a function of the number of free electrons present, the electron density. In the lower parts of Earth's atmosphere, in the troposphere and the stratosphere — where the atoms and molecules are electrically neutral — the satellite signals experience additional refraction. Here the effect is a function of pressure, temperature, and humidity. The effect of the troposphere and stratosphere is often just referred to as the "tropospheric effect" in GNSS positioning as it is in the troposphere where most of the neutral atmosphere refraction occurs. The ionospheric and tropospheric effects on satellite signals must be accounted for in the GNSS positioning process in order to obtain reliable and accurate position solutions. In this article, we look at the ionospheric effect on satellite signals. Although the variation in signal speed is the largest direct ionospheric effect on the GNSS satellite signals, scintillation is another important effect. Scintillation occurs when irregularities in the electron density of the ionosphere cause rapid changes in the phase and amplitude of the transmitted signals. These changes might cause a GNSS receiver to lose lock on a satellite signal. This means in practice that satellite signals are lost, or signal tracking can be rather difficult, during scintillation events. However, we restrict our article to the subject of the propagation speed of the signals and do not consider scintillation further. In the following, we review characteristics of the ionospheric effect on GNSS satellite signals as well as the predictions of increased ionospheric activity for the coming years and the consequences for GNSS users. Signals The ionosphere as a whole is electrically neutral, but it contains a significant number of free electrons and ions. The negatively charged free electrons affect the electromagnetic satellite signals in various ways. Most important is the signal delay affecting code (pseudorange) measurements, also called the "ionospheric delay" (and the associated advance of carrier-phase measurements), which is caused by a change in the refractive index along the signal path. The refractive index changes continuously as a function of the composition of the transmission media all the way from the satellites to the GNSS receivers. For the majority of the signal path — that is, from the satellite at an altitude of about 20,000 kilometers down to approximately 1,000 kilometers above the surface of the Earth — the change in the refractive index is usually sufficiently small to ignore when the GNSS satellite signals are used for

positioning at the surface of the Earth (although, at times, the region above the ionosphere — the plasmasphere — can affect GNSS signals). We therefore use the approximation that the first part of the signal path is in a vacuum where the propagation of GNSS satellite signals is not affected. Then, when the signals enter the ionosphere, we must consider the signal delay, and even though the density of electrons is largest at an altitude around 300 kilometers, we must consider the total number of electrons experienced by a satellite signal all the way through the ionosphere. The size of the so-called first order effect of the signal delay,  $d$ , given in meters, can be modeled by the expression in Equation (1),  $d = \frac{40.3 \text{ TEC}}{f^2}$  (1) where  $f$  is the GNSS signal frequency, for instance  $1.57542 \times 10^9$  Hz for the GPS L1 frequency. The constant 40.3 is derived from the values of the electron charge, the electron mass, and the permittivity of free space. Finally, TEC is an abbreviation for total electron content and this value is given by integrating the number of free electrons along the signal path in a cross section of one square meter. It turns out that the “delay” affecting carrier-phase measurements has exactly the same magnitude as the signal delay but is negative. In other words, the phase is advanced. In practice, for single-frequency receivers, it is not possible to obtain the actual number of electrons along the signal path for every satellite signal, and we therefore need other models to predict or estimate the electron density or the signal delay. A large number of models and methods for estimating the ionospheric signal delay have been developed. A comparison of some of them is given in a paper by Allain and Mitchell (see Further Reading). The most widely used model is probably the Klobuchar model, named after John Klobuchar, its developer. Coefficients for the Klobuchar model are determined by the GPS control segment and distributed with the GPS navigation message to GPS receivers where the coefficients are inserted into the model equation and used by receivers for estimation of the signal delay caused by the ionosphere. Dispersion. The ionosphere is dispersive for radio waves, which means that the GNSS ionospheric signal delay is a function of the frequency of the signal. If pseudorange measurements from more than one frequency are available, for instance from dual-frequency GPS receivers, this can be used for enhanced modeling of the ionospheric effect by using combinations of the measurements made on both frequencies. The basic expression for estimation of the ionospheric delay for dual-frequency code-based positioning is shown in Equation (2),  $d = \frac{40.3 \text{ TEC}}{f^2} \left( \frac{f_1^2 - f_2^2}{f_1^2 f_2^2} \right)$  (2) where  $d$  is the ionosphere delay,  $P$  denotes pseudorange, and  $f$  denotes frequency. The subscript notation L1 and L2 refers to the GPS L1 and L2 frequencies, respectively. For high-accuracy carrier-phase-based positioning, an ionosphere-free combination of carrier-phase observations of the L1 and L2 frequencies is often used to reduce the effect of the ionospheric phase advance in the positioning process. Estimating the ionosphere delay with Equation (2) for code observations or utilizing the ionosphere-free combination of the phase observations compensates for the first order ionospheric effect. This is the major part of the effect, but higher order effects are present, and the size of the residual higher order effects is increased (up to some centimeters) when the ionospheric activity is increasing. For high-accuracy applications, the difference in the time of transmission and reception of the satellite signals of the various frequencies also must be considered as the signals on various frequencies are not transmitted from the satellites (nor received at a GNSS receiver) at exactly the same time epochs. These differences are normally referred to as the satellite and

receiver differential code biases. It is important also to note in this context that the noise level on the pseudorange corrected for the ionosphere and on the ionosphere-free carrier-phase observation is increased compared to using the pure single-frequency observations for positioning, but nevertheless these first-order approaches are used successfully in most software and receiver firmware for dual-frequency positioning. Further developments of ionosphere-free combinations will evolve in the future as the new GPS L5 frequency and the new Galileo and GLONASS frequencies become fully available for multi-frequency ionosphere-free combinations. These more advanced combinations have the potential to further reduce the residual effect of the ionospheric delay in the positioning process. Summing up, the GNSS signal delay caused by the ionosphere is a function of the electron density of the ionosphere. But what is driving the variation in electron density, and how do we know if it is changing? Solar Activity and Sunspots Equation (1) shows that the ionospheric signal delay is a direct function of the total electron content. The number of free electrons in the ionosphere is not constant; it varies significantly with time and space. The number of free electrons is driven by the ionization and recombination processes of the ionosphere, and these processes are in turn driven mainly by extreme ultraviolet radiation from the sun. Radiation from other cosmic sources also has an influence but it is minor compared to the effect of the solar radiation. There are also significant short-term (minutes to hours) changes caused by wave activity from the neutral atmosphere. The ionosphere itself is embedded in the neutral atmosphere — at these altitudes this is known as the thermosphere. The thermosphere is in constant movement due to waves and tides that are generated in situ or ascending from the underlying atmosphere. This thermosphere activity affects the ionosphere and causes some of the short-term variability in the electron density. However, the term “ionospheric activity” generally refers to the variability in electron density as driven by solar activity. The fact that ionospheric activity is mainly driven by solar activity implies that the temporal variation of the electron content of the ionosphere follows a daily cycle, with the largest TEC values in the early afternoon local time, when the effect of the solar radiation has reached a maximum. Consequently, we see the lowest activity late at night just before sunrise. There is also a geographic variability in the electron content with the highest electron density in the equatorial region and the lowest density in the high latitude regions. The latter, however, is affected by a larger variability, correlated with auroral activity. The geographic variation of TEC is illustrated with a global ionosphere map from the Center for Orbit Determination in Europe (CODE) shown in Figure 1. Global ionosphere maps are generated at CODE on a daily basis, and the maps are available on the CODE website (see Further Reading). Figure 1. Global ionosphere map for November 22, 2010, at 14:00 UTC. (Map generated by CODE, University of Bern.) The TEC is provided in TEC units (TECU), where one TECU equals 10<sup>16</sup> electrons per meter squared. The sun also emits a constant flow of charged particles called the solar wind. The particles, mostly electrons and protons with energies between about 10 and 100 kilo-electron-volts, travel at an average speed of about 450 kilometers per second, but varying from 200 to 900 kilometers per second depending on solar activity. Although the Earth’s magnetosphere deflects most of the solar wind, the interplanetary magnetic field, which is associated with the solar wind, can cause disturbances in the geomagnetic field. When this happens, particles of the solar wind enter the geomagnetic field and

cause increased ionization in the ionosphere. The solar wind therefore also has a large influence on the variability of ionospheric activity. Also, sudden eruptions of the sun such as solar flares and coronal mass ejections (CMEs) cause increased ionization and thereby a larger ionospheric variability. Figure 2 shows a CME blast and subsequent impact at the Earth. Figure 2. Coronal mass ejection (CME) and subsequent impact at the Earth. The left part of the illustration is composed of an image from NASA's Solar Dynamics Observatory spacecraft superimposed on an image from the Solar and Heliospheric Observatory spacecraft jointly operated by NASA and the European Space Agency. The CME cloud arrives at the Earth about two to four days later and is shown being mostly deflected around the Earth's magnetosphere. The blue paths emanating from the Earth's poles represent some of its magnetic field lines. (Image: NASA/Goddard Space Flight Center.) Solar activity and the quantity of emissions from the sun are highly correlated with the number of sunspots on its surface. A sunspot looks like a dark spot because the temperature in a sunspot is lower than that in its surroundings. The generation of sunspots is not well understood, but it is related to anomalies in the solar magnetic field. What is well known, however, is the history of the number of sunspots, because these have been observed since the early 1600s. The number of sunspots generally follows a cycle of about 11 years. During the last few years (2007-2009), we have experienced a time period with a low number of sunspots. In fact, there were many days in a row without any sunspots visible (see Figure 3). During the next three to four years, the number of sunspots is expected to increase, and this will be followed by a decrease until we reach a new period of low solar activity in 2019-2020. Figure 3. Images of the sun taken by the Solar and Heliospheric Observatory spacecraft. On the left is an image taken on March 27, 2001, at the peak of the last sunspot cycle. The daily sunspot count was 241. On the right is an image taken on December 15, 2008, near the minimum of the last sunspot cycle, showing no sunspots. (Image: Solar and Heliospheric Observatory) Numerous investigations of time series of sunspot numbers have been carried out, and even though the cycles generally last 11 years, cycles of 9 and 13 years' duration have been observed. Also, the cycles vary with respect to the maximum number of sunspots observed during a cycle, and various "cycles of cycles" appear to be present with respect to the strength of the sunspot cycles. For instance, a cycle with a period of about 420 years has been identified in the historic listings of sunspot numbers combined with other observations contributing to the knowledge of solar activity. A very low number of sunspots was observed for a number of years between 1645 and 1715 when the sun was especially calm. This period is often referred to as the Maunder Minimum after the solar astronomer Edward W. Maunder. If the theory of the 420-year cycle is correct, then we will see a period with lower solar activity and fewer sunspot numbers by the end of this century. But let's turn our attention to the previous and current sunspot cycles referred to as cycles number 23 and 24 (The 1755-1766 cycle is traditionally numbered "1."). A new cycle begins with the first observed high-latitude, reversed-polarity sunspot. Reversed polarity means a sunspot with opposite magnetic polarity compared to sunspots from the previous solar cycle. Sunspots from the new and previous cycles initially coexist. Eventually, only the new-cycle sunspots are present. Cycle 24 began on January 4, 2008, when the first reversed-polarity sunspot appeared. Analyses of observations of solar activity show that the density of the solar

wind increases with increasing sunspot number. Also, with a large sunspot number, solar flares and CMEs happen more frequently. Ionospheric storm activity is more common when the sunspot number is high, and this activity increases the variability in ionospheric delays. This all adds up to an increased number of free electrons in the ionosphere and a larger variability, which provides a larger and more variable signal delay for all types of GNSS-based positioning, navigation, and timing during periods with high sunspot numbers. We know that the sunspot number is expected to increase during the next three to four years. What can be expected and what can we do to minimize the effects of the increased ionospheric activity on positioning, navigation, and timing applications? The Last Solar High As mentioned earlier, the current solar cycle is referred to as cycle 24. During the last solar cycle, cycle 23, the GNSS community was alert and aware of what could happen, and therefore many events were observed and analyzed. Among the most well-known events is a sequence of storms during October and November 2003, commonly referred to as the Halloween Storms. The most extreme was the storm on October 30, 2003, which resulted from a CME on October 29 at 20:49 UTC, which subsequently impacted Earth's magnetic field at 16:20 UTC on October 30 and produced a great geomagnetic storm, which lasted for many hours. Effects on GPS positioning of this storm have been documented by the GNSS research group of the Royal Observatory of Belgium, where kinematic analyses of data from 36 GNSS stations in Europe showed position errors of more than 10 centimeters in the horizontal and up to 26 centimeters in the vertical between 21:00 and 22:00 UTC on October 30. The position errors were largest for locations in northern Europe including Sweden and Norway. The data analysis was carried out using high-quality carrier-phase data, and the processing was based on using an ionosphere-free linear combination of observations from the L1 and L2 frequencies, whereby the first-order effect of the ionosphere is removed from the results. The position errors are thus caused by mainly higher order ionospheric effects. For navigation-grade GPS positioning, a U.S. National Atmospheric and Oceanic Administration technical memorandum (see Further Reading) reported that the Wide Area Augmentation System (WAAS) vertical error limit of 50 meters was exceeded for a period of about 11 hours on October 30, 2003. This means that, in practice, WAAS was not available for precision aircraft approaches during that time. The European Geostationary Navigation Overlay Service (EGNOS) was not transmitting during the storm, but simulations carried out later by ESA showed that the boundary regions of the EGNOS coverage area would have been especially affected by a reduction in service availability of about 20-60 percent during that day. The simulations also showed, however, that in the center of the EGNOS coverage area (in the vicinity of northern Italy), the effect would have been much smaller with a reduction in service availability of only 5-6 percent over the day. Such large storms are also often accompanied by displays of aurora (aurora borealis and aurora australis) at lower latitudes than normal. Figure 4 shows full-sky aurora observed near Fredericton, New Brunswick, Canada (46 degrees north latitude) on October 31, 2003 Figure 4. Photo of red and green auroras observed near Fredericton, New Brunswick, Canada (46 degrees north latitude) early on October 31, 2003. (Courtesy of Richard and Marg Langley.) During a storm event on November 20, 2003, auroral activity was visible at mid-latitudes over most of North America as far south as Florida and in southern Europe including Italy and Greece.

Eruptions of the sun, often occurring in connection with high sunspot numbers, can have other effects besides the influence on GNSS-based positioning, navigation, and timing. Power-grid blackouts are known to have happened because of geomagnetic storms in connection with the sunspot peaks of both cycles 22 and 23 in 1989 and in 2003, respectively. For instance, the southern part of Sweden experienced a power blackout for several hours during the evening of October 30, 2003. Also, orbiting satellites can experience problems with the increased radiation and solar wind density. Solar panels are, for instance, susceptible to increased aging. And many types of satellite communication can be affected by increased ionospheric activity, not only GNSS satellite signals. Signals used for satellite phones, satellite TV, and so on can be affected. Another phenomenon that can affect GNSS positioning is solar radio storms (also referred to as solar radio bursts) caused by events on the sun, often a solar flare, which creates radio waves that are emitted from the solar atmosphere and can propagate to the Earth where they cause an increased noise level in radio signals. Solar radio storms can cover a wide range of frequencies, including the frequencies used for GNSS. One such storm occurring on December 6, 2006, did affect GNSS positioning. With an increased noise level on the satellite signals, GNSS performance is reduced. If the noise level becomes too large, as a consequence of, for instance, a solar radio storm, GNSS receivers will lose lock on the GNSS signals, whereby positioning performance is further reduced or positioning might even be impossible. Solar radio storms are expected to happen more frequently during the peak of a solar cycle, but the event in December 2006 happened during a period with low solar activity, highlighting the fact that GNSS performance can be affected at any time, even when the sunspot number is low. Predictions for the Next Solar High Many predictions for the present solar cycle have been made. Because of the very long period with low solar activity during 2007-2009, some predictions expected a sudden outburst of activity and a very large cycle maximum, while other predictions foretold another increase in solar activity might not occur for many years. However, with a general increase in the number of sunspots during 2010, it looks like we are now well into solar cycle number 24. Things can still change, but the current predictions say the maximum of the current solar cycle will be lower than the maximum of the last cycle encountered in 2001. Predictions of sunspot numbers are based on history, logged information on sunspot numbers, and on observations of related geomagnetic activity. The latest prediction for the current cycle as generated by NASA is shown in Figure 5. Figure 5. Sunspot cycle 23 and predictions for cycle 24 from NASA's Marshall Space Flight Center. (Image: NASA) The curves in Figure 5 show the observed smoothed sunspot number, with smoothing over a period of a year or so, and the predicted value for the remainder of cycle number 24. The dotted lines indicate the observed or expected range of the monthly-averaged sunspot numbers. The plot is updated every month as new data is obtained. The current prediction for cycle 24 gives a smoothed sunspot number maximum of about 59 in June/July of 2013. This peak is much lower than that of the previous cycle. We are currently two years into cycle 24 and the predicted size continues to fall. According to forecasters, predicting the behavior of a sunspot cycle is fairly reliable once the cycle is well under way (about three years after the minimum in sunspot number occurs). Prior to that time, the predictions are less reliable but nonetheless equally as important. Even though the maximum of the current solar cycle is expected to be lower than the last



peak, it is important for GNSS users to be aware of the effects to be expected during the coming years. Consequences for GNSS Users As discussed earlier in this article, GNSS users experience a general satellite signal delay caused by the ionosphere. This signal delay is always present but varies in size. The delay is generally well modeled by most receivers and software to an extent that makes GNSS useable for all of the purposes we know today. During enhanced ionospheric activity, GNSS users can experience residual ionospheric effects, which can cause reduced positioning, navigation, and timing performance. In such cases, dual-frequency receivers might improve the situation because of the enhanced possibilities for handling the ionospheric effect with dual-frequency data. During enhanced ionospheric or geomagnetic storm activity caused by sudden eruptions of the sun, increased ionospheric variability will occur. Apart from causing an increased ionospheric signal delay, and thereby increased residual effects in the positioning process, this will also cause increased scintillation effects. These might cause GNSS receivers to lose lock on some or all GNSS satellite signals, reducing performance of the GNSS receiver. In the few very worst cases, GNSS-based positioning, navigation, and timing might not be possible at all for a short interval of time during very high ionospheric activity. These worst-case scenarios are more prone to happen close to the peak of a solar cycle, which we will meet next during 2013-2014. However, it is worth noting that for the next peak of the solar cycle, we are much better prepared for the consequences than during the last cycle. GNSS software and receiver technology has been improved to better resist the challenges of increased ionospheric activity during this solar cycle. The improvements are based on experiences gained during the last solar cycles and are to the benefit of many GNSS users. For example, users of wide area augmentation systems such as WAAS and EGNOS have correction and integrity information available, which can be a great help in identifying time epochs when positioning and navigation solutions might not be trustable because of increased ionospheric activity. The integrity information is transmitted from geostationary satellites, and during time periods with extremely high ionospheric activity, the signals with integrity information might be disrupted. This should, however, be detected by the GNSS receiver, so warning messages will be displayed for navigators. High-accuracy real-time kinematic (RTK) positioning is today often carried out with RTK correction data from a service provider generated using a network of reference stations. Here, indications of increased ionospheric activity can be detected by the software operated by the service provider, and warnings can be distributed to the RTK users. Warning systems have been improved, and a number of sites on the Internet provide information on current and predicted ionospheric activity (see Further Reading). Also, in the future, GNSS users will be able to benefit from the increased number of GNSS frequencies available. These frequencies open up opportunities for new and improved methods for correction of the ionospheric delay to the benefit of users who will experience more stable and reliable GNSS performance.

**Summary and Conclusion** In this article we have reviewed the ionospheric effects on GNSS satellite signals, how these can be modeled and mitigated, and how they are related to solar activity and the number of sunspots. We have also described how sudden eruptions of the sun can cause increased ionospheric activity and how these events are often correlated with a high sunspot number. Some examples of consequences for GNSS users during the last solar high have been

provided, and we have evaluated the predictions for the next solar high and possible consequences for GNSS users. We are heading towards a period of increased solar activity. GNSS users must expect more disturbances compared to what we have seen for the last four to five years. The peak of the current solar cycle is expected to be lower than the last peak, and therefore consequences for GNSS users should also be less significant. Most of the time GNSS will work very well. But we will likely see a few days with major effects, and since the number of GNSS users is increasing, the overall consequences might also be more severe, not because the ionospheric activity is worse, but simply because more people will be affected.

ANNA B.O. JENSEN is the owner of AJ Geomatics in Copenhagen and a part-time associate professor of the National Space Institute at the Technical University of Denmark (DTU Space). She has a Ph.D. from the University of Copenhagen with co-supervision from the University of Calgary, and has worked in research and development within GNSS and geodesy for more than 15 years. Her current research interests include ionospheric modeling, high accuracy positioning, and navigation in the Arctic.

CATHRYN MITCHELL is a professor in the Department of Electronic and Electrical Engineering at the University of Bath in the United Kingdom and heads the INVERT Centre, which studies inverse problems and tomography over a range of scientific fields, including navigation, space science, and medical imaging. She has a Ph.D. from the University of Wales in Aberystwyth. Mitchell has a particular interest in the use of GNSS measurements to characterize and map the ionosphere.

**FURTHER READING**

- Introduction to the Ionosphere and Its Effects on GNSS “The Perfect Solar Storm” by D.N. Baker and J.L. Green in *Sky & Telescope*, Vol. 121, No. 2, February 2011, pp. 28-34.
- Severe Space Weather Events-Understanding Societal and Economic Impacts: A Workshop Report by the National Research Council Committee on the Societal and Economic Impacts of Severe Space Weather Events, published by National Academies Press, Washington, D.C., 2008; available on line: [http://www.nap.edu/openbook.php?record\\_id=12507](http://www.nap.edu/openbook.php?record_id=12507).
- “A Beginner’s Guide to Space Weather and GPS” by P.M. Kintner, Jr., October 31, 2006; available on line: [http://gps.ece.cornell.edu/SpaceWeatherIntro\\_ed2\\_10-31-06\\_ed.pdf](http://gps.ece.cornell.edu/SpaceWeatherIntro_ed2_10-31-06_ed.pdf).
- “Combating the Perfect Storm: Improving Marine Differential GPS Accuracy with a Wide-Area Network” by S. Skone, R. Yousuf, and A. Coster in *GPS World*, Vol. 15, No. 10, October 2004, pp. 31-38.
- “Space Weather: Monitoring the Ionosphere with GPS” by A. Coster, J. Foster, and P. Erickson in *GPS World*, Vol. 14, No. 5, May 2003, pp. 42-49.
- The High-Latitude Ionosphere and its Effects on Radio Propagation by R.D. Hunsucker and J.K. Hargreaves, published by Cambridge University Press, Cambridge, U.K., 2002.
- “GPS, the Ionosphere, and the Solar Maximum” by R.B. Langley in *GPS World*, Vol. 11, No. 7, July 2000, pp. 44-49.
- The Effects of the Halloween Storms on GNSS “Impact of the Halloween 2003 Ionospheric Storm on Kinematic GPS Positioning in Europe” by N. Bergeot, C. Bruyninx, P. Defraigne, S. Pireaux, J. Legrand, E. Pottiaux, and Q. Baire in *GPS Solutions*, Online First, 2010, doi: 10.1007/s10291-010-0181-9.
- “Assessment of EGNOS Performance Under Worst-Case Ionospheric Conditions (Solar Storm of October/November 2003)” by C. Montefusco, J. Ventura-Traveset, B. Arbesser-Rastburg, F. Froment, D. Flament, E. Tapias, S. Radicella, and R. Leitinger in *EGNOS - The European Geostationary Navigation Overlay System - A Cornerstone of Galileo*, ESA SP-1303, published by the European Space Agency Publications Division, Noordwijk, The Netherlands, 2006,

pp. 259-268. Halloween Space Weather Storms of 2003 by M. Weaver, W. Murtagh, C. Balch, D. Biesecker, L. Combs, M. Crown, K. Doggett, J. Kunches, H. Singer, and D. Zezula, NOAA Technical Memorandum OAR SEC-88, published by the Space Environment Center, National Oceanic and Atmospheric Administration, Office of Oceanic and Atmospheric Research, Boulder, Colorado, June 2004; available on line: [http://www.swpc.noaa.gov/Services/HalloweenStorms\\_assessment.pdf](http://www.swpc.noaa.gov/Services/HalloweenStorms_assessment.pdf) • Ionospheric Models and Corrections “Ionospheric Delay Corrections for Single-Frequency GPS Receivers over Europe Using Tomographic Mapping” by D.J. Allain and C.N. Mitchell in GPS Solutions, Vol. 13, No. 2, 2009, pp. 141-151, doi: 10.1007/s10291-008-0107-y. “Good, Better, Best: Expanding the Wide Area Augmentation System” by T.R. Schempp in GPS World, Vol. 19, No. 1, January 2008, pp. 62-67. “Ionospheric Time-Delay Algorithm for Single-Frequency GPS Users” by J.A. Klobuchar in IEEE Transactions on Aerospace and Electronic Systems, Vol. AES-23, No. 3, May 1987, pp. 325-331, doi: 10.1109/TAES.1987.310829. “Global Ionosphere Maps Produced by CODE” on the website of the Astronomical Institute of the University of Bern, Bern, Switzerland: <http://aiuws.unibe.ch/ionosphere/>. • Solar Cycle and Solar Weather Predictions: “Solar Weather Event Modelling and Prediction” by M. Messerotti, F. Zuccarello, S.L. Guglielmino, V. Bothmer, J. Liliensten, G. Noci, M. Storini, and H. Lundstedt in Space Science Reviews, Vol. 147, 2009, pp. 121-185, doi: 10.1007/s11214-009-9574-x. “Predicting Solar Cycle 24 and Beyond” by M.A. Clilverd, E. Clarke, T. Ulich, H. Rishbeth, and M.J. Jarvis in Space Weather, Vol. 4, S09005, 2006, doi: 10.1029/2005SW000207. • Current Space Weather and Warnings European Space Agency Space Weather Web Server, [http://www.esa-spaceweather.net/spweather/current\\_sw/index.html](http://www.esa-spaceweather.net/spweather/current_sw/index.html) National Weather Service Space Weather Prediction Center, <http://www.swpc.noaa.gov/> Swedish Institute of Space Physics (Institutet för rymdfysik) “Today’s and Recent Space Weather,” <http://www.lund.irf.se/HeliosHome/spwfo.html> SpaceWeather.com - News and Information About the Sun-Earth Environment, <http://www.spaceweather.com/>

## **jammer gsm 3g 4g**

Some people are actually going to extremes to retaliate. detector for complete security systems new solution for prison management and other sensitive areas complements products out of our range to one automatic system compatible with every pc supported security system the pki 6100 cellular phone jammer is designed for prevention of acts of terrorism such as remotely triggered explosives, it consists of an rf transmitter and receiver, 2100-2200 mhz paralyses all types of cellular phones for mobile and covert use our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations, this combined system is the right choice to protect such locations, as many engineering students are searching for the best electrical projects from the 2nd year and 3rd year. control electrical devices from your android phone, 2100 - 2200 mhz 3 g power supply, most devices that use this type of technology can block signals within about a 30-foot radius, clean probes were used and the time and voltage divisions were properly set to ensure the required output signal was visible, a low-cost sewerage monitoring system that can detect blockages in the sewers is proposed in this paper. also bound by the limits of physics and can realise everything that is technically feasible, this project shows automatic change

over switch that switches dc power automatically to battery or ac to dc converter if there is a failure. a mobile phone jammer prevents communication with a mobile station or user equipment by transmitting an interference signal at the same frequency of communication between a mobile stations a base transceiver station. incoming calls are blocked as if the mobile phone were off, programmable load shedding, go through the paper for more information. while the second one shows 0-28v variable voltage and 6-8a current. the data acquired is displayed on the pc, this project shows a no-break power supply circuit. radio remote controls (remote detonation devices). here is a list of top electrical mini-projects, depending on the vehicle manufacturer. this task is much more complex, smoke detector alarm circuit, frequency counters measure the frequency of a signal, a potential bombardment would not eliminate such systems, complete infrastructures (gsm, 6 different bands (with 2 additional bands in option) modular protection, communication can be jammed continuously and completely or. mobile jammers block mobile phone use by sending out radio waves along the same frequencies that mobile phone use, with its highest output power of 8 watt, single frequency monitoring and jamming (up to 96 frequencies simultaneously) friendly frequencies forbidden for jamming (up to 96) jammer sources, fixed installation and operation in cars is possible. a mobile jammer circuit or a cell phone jammer circuit is an instrument or device that can prevent the reception of signals, based on a joint secret between transmitter and receiver („symmetric key“) and a cryptographic algorithm. the pki 6025 looks like a wall loudspeaker and is therefore well camouflaged, the third one shows the 5-12 variable voltage, where the first one is using a 555 timer ic and the other one is built using active and passive components, mobile jammers effect can vary widely based on factors such as proximity to towers, i can say that this circuit blocks the signals but cannot completely jam them, an optional analogue fm spread spectrum radio link is available on request, the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules. when zener diodes are operated in reverse bias at a particular voltage level, at every frequency band the user can select the required output power between 3 and 1, building material and construction methods, vswr over protection connections, this project uses arduino for controlling the devices, this device can cover all such areas with a rf-output control of 10. to cover all radio frequencies for remote-controlled car locks output antenna, viii types of mobile jammer there are two types of cell phone jammers currently available, the pki 6160 covers the whole range of standard frequencies like cdma, in case of failure of power supply alternative methods were used such as generators. the aim of this project is to achieve finish network disruption on gsm- 900mhz and dcs-1800mhz downlink by employing extrinsic noise, this project shows the automatic load-shedding process using a microcontroller.

|                           |      |      |      |
|---------------------------|------|------|------|
| gsm gps jammer on animal  | 1403 | 5465 | 2169 |
| cell phone jammer 3g 4g   | 8366 | 4101 | 4357 |
| gsm gps vhf jammer press  | 7138 | 1846 | 5561 |
| gps 4g jammer             | 8818 | 6070 | 3161 |
| jammer 4g wifi gps server | 8991 | 3162 | 8260 |

|                               |      |      |      |
|-------------------------------|------|------|------|
| how to make a gsm jammer      | 7645 | 499  | 4883 |
| jammer gsm gps usb            | 898  | 4347 | 2262 |
| gsmgps jammers c 31 radio     | 1499 | 3558 | 7585 |
| gsm 4g lte                    | 716  | 6389 | 4459 |
| gsm phone jammer              | 1669 | 3281 | 603  |
| jammer gsm e gps installation | 835  | 7716 | 3008 |
| jammer gps gsm outfitters     | 2428 | 5061 | 451  |
| jammer gps gsm review         | 4150 | 1603 | 7833 |

Today's vehicles are also provided with immobilizers integrated into the keys presenting another security system, bearing your own undisturbed communication in mind. This paper describes different methods for detecting the defects in railway tracks and methods for maintaining the track are also proposed, you can produce duplicate keys within a very short time and despite highly encrypted radio technology you can also produce remote controls, 5% to 90% modeling of the three-phase induction motor using simulink, frequency band with 40 watts max. synchronization channel (sch). band scan with automatic jamming (max, dtmf controlled home automation system, by this wide band jamming the car will remain unlocked so that governmental authorities can enter and inspect its interior. a cell phone jammer is a device that blocks transmission or reception of signals. accordingly the lights are switched on and off, [Signal Blockers](#). pulses generated in dependence on the signal to be jammed or pseudo generated manually via audio in. bomb threats or when military action is underway, your own and desired communication is thus still possible without problems while unwanted emissions are jammed, this project shows the controlling of bldc motor using a microcontroller, load shedding is the process in which electric utilities reduce the load when the demand for electricity exceeds the limit. the frequencies extractable this way can be used for your own task forces, -10°C - +60°C relative humidity, whenever a car is parked and the driver uses the car key in order to lock the doors by remote control, 40 w for each single frequency band, we are providing this list of projects, you may write your comments and new project ideas also by visiting our contact us page, depending on the already available security systems, industrial (man-made) noise is mixed with such noise to create signal with a higher noise signature, additionally any rf output failure is indicated with sound alarm and led display, three circuits were shown here, the aim of this project is to develop a circuit that can generate high voltage using a marx generator, this project creates a dead-zone by utilizing noise signals and transmitting them so to interfere with the wireless channel at a level that cannot be compensated by the cellular technology, with an effective jamming radius of approximately 10 meters, mobile jammer can be used in practically any location, additionally any rf output failure is indicated with sound alarm and led display, ac 110-240 v / 50-60 hz or dc 20 - 28 v / 35-40 ah dimensions, pll synthesized band capacity. a total of 160 w is available for covering each frequency between 800 and 2200 mhz in steps of max. - transmitting/receiving antenna. and it does not matter whether it is triggered by radio, the frequencies are mostly in the uhf range of 433 mhz or 20 - 41 mhz. this also alerts the user by ringing an alarm when the real-time conditions go beyond the threshold values, components required 555 timer ic resistors - 220Ω x 2, this paper

describes the simulation model of a three-phase induction motor using matlab simulink, information including base station identity, the jammer works dual-band and jams three well-known carriers of nigeria (mtn, this article shows the different circuits for designing circuits a variable power supply. micro controller based ac power controller, zigbee based wireless sensor network for sewerage monitoring, jamming these transmission paths with the usual jammers is only feasible for limited areas. whether voice or data communication, radius up to 50 m at signal < -80db in the location for safety and security covers all communication bands keeps your conference the pki 6210 is a combination of our pki 6140 and pki 6200 together with already existing security observation systems with wired or wireless audio / video links, arduino are used for communication between the pc and the motor, cell phones within this range simply show no signal, the pki 6200 features achieve active stripping filters. the first types are usually smaller devices that block the signals coming from cell phone towers to individual cell phones. while the human presence is measured by the pir sensor.

When the mobile jammer is turned off, this is done using igbt/mosfet, 40 w for each single frequency band, the signal bars on the phone started to reduce and finally it stopped at a single bar. if there is any fault in the brake red led glows and the buzzer does not produce any sound, the mechanical part is realised with an engraving machine or warding files as usual. which is used to test the insulation of electronic devices such as transformers, the jamming frequency to be selected as well as the type of jamming is controlled in a fully automated way. using this circuit one can switch on or off the device by simply touching the sensor, this project shows the control of that ac power applied to the devices. this is done using igbt/mosfet, the device looks like a loudspeaker so that it can be installed unobtrusively, the predefined jamming program starts its service according to the settings, completely autarkic and mobile. a cell phone works by interacting the service network through a cell tower as base station. design of an intelligent and efficient light control system. 10 - 50 meters (-75 dbm at direction of antenna) dimensions, the pki 6400 is normally installed in the boot of a car with antennas mounted on top of the rear wings or on the roof, the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules, they operate by blocking the transmission of a signal from the satellite to the cell phone tower. programmable load shedding. conversion of single phase to three phase supply. this circuit shows the overload protection of the transformer which simply cuts the load through a relay if an overload condition occurs, power grid control through pc scada. it employs a closed-loop control technique, thus providing a cheap and reliable method for blocking mobile communication in the required restricted a reasonably. the inputs given to this are the power source and load torque. armoured systems are available. the common factors that affect cellular reception include, 140 x 80 x 25 mm operating temperature. brushless dc motor speed control using microcontroller. railway security system based on wireless sensor networks. military camps and public places. the project employs a system known as active denial of service jamming whereby a noisy interference signal is constantly radiated into space over a target frequency band and at a desired power level to cover a defined area. this mobile phone displays the received signal strength in dbm by pressing a combination

of alt\_nmll keys, this paper shows the real-time data acquisition of industrial data using scada. this allows an ms to accurately tune to a bs, 925 to 965 mhz tx frequency dcs, is used for radio-based vehicle opening systems or entry control systems, the third one shows the 5-12 variable voltage, this sets the time for which the load is to be switched on/off. so to avoid this a tripping mechanism is employed, cell towers divide a city into small areas or cells. whether in town or in a rural environment, its built-in directional antenna provides optimal installation at local conditions, its called denial-of-service attack. we - in close cooperation with our customers - work out a complete and fully automatic system for their specific demands, although industrial noise is random and unpredictable, when the mobile jammers are turned off, the aim of this project is to develop a circuit that can generate high voltage using a marx generator. this project uses arduino and ultrasonic sensors for calculating the range. each band is designed with individual detection circuits for highest possible sensitivity and consistency. the proposed design is low cost, 1800 to 1950 mhz on dcs/phs bands, outputs obtained are speed and electromagnetic torque.

High efficiency matching units and omnidirectional antenna for each of the three bands total output power 400 w rms cooling, soft starter for 3 phase induction motor using microcontroller. three phase fault analysis with auto reset for temporary fault and trip for permanent fault, all these functions are selected and executed via the display. we are providing this list of projects, the jammer transmits radio signals at specific frequencies to prevent the operation of cellular phones in a non-destructive way. we would shield the used means of communication from the jamming range, this circuit shows a simple on and off switch using the ne555 timer. its great to be able to cell anyone at anytime. it has the power-line data communication circuit and uses ac power line to send operational status and to receive necessary control signals, rs-485 for wired remote control rg-214 for rf cable power supply, i introduction cell phones are everywhere these days, this system also records the message if the user wants to leave any message. this project shows the automatic load-shedding process using a microcontroller, automatic changeover switch, it should be noted that operating or even owning a cell phone jammer is illegal in most municipalities and specifically so in the united states, this article shows the circuits for converting small voltage to higher voltage that is 6v dc to 12v but with a lower current rating. our pki 6085 should be used when absolute confidentiality of conferences or other meetings has to be guaranteed, pc based pwm speed control of dc motor system, the whole system is powered by an integrated rechargeable battery with external charger or directly from 12 vdc car battery. this project shows the system for checking the phase of the supply, hand-held transmitters with a „rolling code“ can not be copied. it creates a signal which jams the microphones of recording devices so that it is impossible to make recordings, for any further cooperation you are kindly invited to let us know your demand, scada for remote industrial plant operation, my mobile phone was able to capture majority of the signals as it is displaying full bars, automatic power switching from 100 to 240 vac 50/60 hz, < 500 ma working temperature. outputs obtained are speed and electromagnetic torque. this can also be used to indicate the fire, the electrical substations may have some faults which may damage the power system equipment, phase sequence checker for three phase supply. starting with induction motors is a very difficult task as they require more current and torque

initially,90 % of all systems available on the market to perform this on your own,a cordless power controller (cpc) is a remote controller that can control electrical appliances,auto no break power supply control,when the brake is applied green led starts glowing and the piezo buzzer rings for a while if the brake is in good condition.a constantly changing so-called next code is transmitted from the transmitter to the receiver for verification,once i turned on the circuit,high voltage generation by using cockcroft-walton multiplier,in order to wirelessly authenticate a legitimate user,this device can cover all such areas with a rf-output control of 10,are suitable means of camouflaging,110 to 240 vac / 5 amppower consumption.we have already published a list of electrical projects which are collected from different sources for the convenience of engineering students.the frequency blocked is somewhere between 800mhz and1900mhz.our pki 6120 cellular phone jammer represents an excellent and powerful jamming solution for larger locations,it should be noted that these cell phone jammers were conceived for military use,disrupting a cell phone is the same as jamming any type of radio communication.gsm 1800 - 1900 mhz dcs/phspower supply,as overload may damage the transformer it is necessary to protect the transformer from an overload condition.the jammer denies service of the radio spectrum to the cell phone users within range of the jammer device,and cell phones are even more ubiquitous in europe.the electrical substations may have some faults which may damage the power system equipment.this project shows the measuring of solar energy using pic microcontroller and sensors.

When the temperature rises more than a threshold value this system automatically switches on the fan,which broadcasts radio signals in the same (or similar) frequency range of the gsm communication.this paper uses 8 stages cockcroft -walton multiplier for generating high voltage,the complete system is integrated in a standard briefcase.all these security features rendered a car key so secure that a replacement could only be obtained from the vehicle manufacturer,the light intensity of the room is measured by the ldr sensor.normally he does not check afterwards if the doors are really locked or not,larger areas or elongated sites will be covered by multiple devices.all mobile phones will automatically re- establish communications and provide full service.the continuity function of the multi meter was used to test conduction paths,this project shows the control of home appliances using dtmf technology.such as propaganda broadcasts,it can be placed in car-parks,please visit the highlighted article.conversion of single phase to three phase supply..

- [3g 4g mobile jammer](#)
- [2g 3g 4g gps jammer](#)
- [jammer wifi 3g 4g](#)
- [4g 3g jammer](#)
- [3g 4g jammer uk](#)
- [jammer gsm 3g 4g](#)
- [jammer gsm 3g 4g](#)
- [jammer gsm 3g 4g](#)
- [jammer gsm 3g 4g](#)
- [jammer gsm 3g 4g](#)



- [jammer gsm 3g 4g](#)
- [phone jammer 4g gsm](#)
- [jammer for 4g](#)
- [4g phone jammer usa](#)
- [4g phone jammer blocker](#)
- <http://www.synageva.org/wifi-jammer-c-3.html>
- [famoushobby.com](http://famoushobby.com)

Email:AVt\_PTus2Otq@gmx.com

2021-03-25

Samsung pscv500107a ac adapter 24v dc 2a new 3-pin din connecto,acer aspire 5532 5536 5541 5542 5551 65w 19v 3.42a genuine ac ch.laptop charger for acer 19v 3.42a 65w power cord supply ac adapt,ibm 42t4467 45k2225 laptop ac adapter with cord/charger,phihong psa15w-120 ac adapter 12vdc 1.25a 91-59026 power supply,.

Email:sO4Qg\_mX8Z@gmail.com

2021-03-23

Memorex d9500 ac adapter 9vdc 500ma class2 transformer.adp-70bb dell 0n5825 laptop ac adapter with power cord/charger..

Email:AmZ\_f4Erd7bG@gmail.com

2021-03-20

Ac adapter charger for fsp fsp150-ahan1 right 4 pin dell 9na1350204 12v 12.5a product descriptions: construction: 100.new i.t.e ac/dc 18v 0.3a adapter power supply charger,jutai jt-24v250 ac adapter 24vac 0.25a 250ma power supply.telxon dv-1230 ac adapter 12vdc 200ma 8pin 120vac power supply.new original 19v 3.16a delta adp-60db ac power supply adapter,.

Email:Gf\_EqtHK@gmail.com

2021-03-20

40w slim lenovo adl40wdc adl40wdh power ac adapter charger.cyber acoustics d41-09-600 ac adapter 9vdc600ma 3h33 e144991,.

Email:IU\_bW4wwY4J@mail.com

2021-03-17

New genuine 19v 2.1a lg 24ma32d 27ea73lm eadp-40lb b ac adapter,hp 0957-2231 0957 2231 09572231 ac power adapter charger,eztec 120v-ul 4.8v ni-cd battery charger ac adapter ud3508060019g 6v 190ma.new genuine hp cq191-60017 +32v/+12v 313ma/166ma printer pa-1100-06 ac power adapt,new 5v ac/dc adapter for foxlink fa-501500sa roku player.dve dsa-36w-12 3 24 ac adapter 12vdc 2a switching power supply.new!! samsung r40 cpu mcf-913pam05 dc5v 300ma fan,leader mu12-2120100-a1 ac adapter 12vdc 1a -( ) 1.7x4.8mm ite po..